

Handwashing unit for motor vehicles

The Handeman

For hot water hand washing in or on trailers, motor vehicles, vans and trucks

The Handeman Original for motor vehicles is fully automatic and only powers up when the battery is fully charged and the engine is running so there is no drain on the battery.

The Handeman is provided in 12 and 24 volt versions.

12V: 180W, 15A

12V low wattage: 90W, 8A.

24V: 250W, 12 A

Certification

VCA registration number: VCS377871

E11 Approval No: 10R-055528, Extension No: 01

General Products Safety Directive: EN-60335-1:2013+A13:2017 and EN 6035-2-62:2003

End of Life Directive: EC Directive 2000/53/EC



at tealwash.com

The Handeman provides a minimum of ten 12 second hand washes per filling – enough for a hard day's work – providing hot water with fingertip tap operation.

water with inigertip tap operation.

For hot water hand

washing in commercial vehicles

Handeman Original mobile sinks for motor vehicles are the perfect solution for those that need a hot water hand wash on the move.

It simply connects to the vehicle's electricity supply, ensuring hot water is always to hand: no plumbing is required.

The Handeman Original for motor vehicles is supplied in a practical 2 tone grey colour.

All Handeman models have a detachable bowl which retains the dirty water, removing the need for a separate waste pipe or waste water storage container.

The Handeman Original is available in 12 and 24 volt versions.

It's robustly constructed in hi-impact polyethylene enabling it to stand up to the rough and tumble of on the road use.

Hot water hand washing benefits from an ideal water temperature of 38-43°C.

Specification

- Weight: 3kg (dry), 5kg (full)
- Height: 335mm
- Width: 300mmDepth: 175mm (closed), 315mm (open)
- · Capacity: 2.2 litres
- Washes per filling: 10.

Construction

• The body is fully moulded in high impact polyethylene.

Optional Extras

- Paper towel holder (GENTWLHDR).
- Soap dispenser and bracket (GENSOAPDISP/BRKT).



Hot water hand

washing benefits from an ideal water temperature of

38°C - 43°C.







Teal Patents Ltd

Unit 2, Chelmsley Wood Industrial Estate Waterloo Avenue, Chelmsley Wood Birmingham B37 6QQ, UK Tel: +44 (0) 121 770 0593 www.tealwash.com Email: enquiries@tealwash.com